E3 Series Variable Frequency Drive Datasheet

Model: E3-210058-1042

1.5 HP (1.1 kW), 5.8 A, 110-115 V, 1-3PH
IP20 Variable Frequency Drive



Input Ratings

Supply Voltage	110-115 V
Input Phases	1
Supply Current Continuous	21.9 A
Supply Fuse or MCB (Type B)	32 A

Output Ratings

Motor Output Rating	1.5 HP (1.1 kW)
Output Voltage	0 to 2 x Supply Voltage
Output Current	5.8 A

Cable Information

Max Supply Cable Size	8 AWG (8 mm²)
Max Motor Cable Size	8 AWG (8 mm²)
Max Motor Cable Length	328 ft (100 m)

Factory Build Options

EMC Filter	No Internal EMC Filter
Brake Transistor	Internal Brake Transistor
Minimum Brake Resistance	100 Ω
Enclosure	IP20
Display	LED
Communication Protocols	ModbusRTU, CANopen, and more*

Drive Dimensions

Size	2
Height	8.7 in (221 mm)
Width	4.33 in (110 mm)
Depth	5.91 in (150 mm)
Weight	3.75 lbs (1.7 kg)
Fixings	4 x M5

Packaged Dimensions

Height	9.21 in (234 mm)
Width	5.67 in (144 mm)
Depth	10.24 in (260 mm)
Weight	4.19 lbs (1.9 kg)

* Consult factory for additional communication options.

Drive color depicted doesn't reflect actual drive color
Black Outershell - RAL Name: Jet Black | RAL Number: 9005 | Hex Code #0A0A0A
Gray Door - RAL Name: Traffic White | RAL Number: 9016 | Hex Code #F6F6F6

Bardac Drives 40 Log Canoe Circle, Stevensville, MD 21666 USA
Phone (410) 604-3400 Fax (410) 604-3500 www.bardac.com AutomationThings.com