

E3 Series Variable Frequency Drive Datasheet

Model: E3-320180-3F4A

5 HP (4 kW), 18 A, 200-240 V, 3PH

IP66 Outdoor Non-switched Variable Frequency Drive with EMC Filter

Input Ratings

Supply Voltage	200-240 V
Input Phases	3
Supply Current Continuous	20.9 A
Supply Fuse or MCB (Type B)	32 A

Output Ratings

Motor Output Rating	5 HP (4 kW)
Output Voltage	0 to Supply Voltage
Output Current	18 A

Cable Information

Max Supply Cable Size	8 AWG (8 mm ²)
Max Motor Cable Size	8 AWG (8 mm ²)
Max Motor Cable Length	328 ft (100 m)

Factory Build Options

EMC Filter	Internal EMC Filter
Brake Transistor	Internal Brake Transistor
Minimum Brake Resistance	50 Ω
Enclosure	NEMA 4X (IP66) Non Switched
Display	LED
Communication Protocols	ModbusRTU, CANopen, and more*

Drive Dimensions

Size	3
Height	12.2 in (310 mm)
Width	8.31 in (211 mm)
Depth	8.86 in (225 mm)
Weight	14.55 lbs (6.6 kg)
Fixings	4 x M4

Packaged Dimensions

Height	12.01 in (305 mm)
Width	10.63 in (270 mm)
Depth	17.32 in (440 mm)
Weight	16.76 lbs (7.6 kg)

* Consult factory for additional communication options.

Drive color depicted doesn't reflect actual drive color
Black Outershell - RAL Name: Jet Black | RAL Number: 9005 | Hex Code #0A0A0A
Gray Door - RAL Name: Traffic White | RAL Number: 9016 | Hex Code #F6F6F6

