

P2 Series Variable Frequency Drive Datasheet

Model: P2-26020-3H04A-T

2 HP (1.5 kW), 3.1 A, 500-600 V, 3PH

IP66 Non Switched Outdoor Variable Frequency Drive with TFT Display

Input Ratings

Supply Voltage	500-600 V
Input Phases	3
Supply Current Continuous	3.7 A
Supply Fuse or MCB (Type B)	10 A

Output Ratings

Motor Output Rating	2 HP (1.5 kW)
Output Voltage	0 to Supply Voltage
Output Current	3.1 A

Cable Information

Max Supply Cable Size	8 AWG (8 mm ²)
Max Motor Cable Size	8 AWG (8 mm ²)
Max Motor Cable Length	328 ft (100 m)

Factory Build Options

EMC Filter	No Internal EMC
Brake Transistor	Internal
Minimum Brake Resistance	300 Ω
Enclosure	NEMA 4X (IP66) Non Switched
Display	TFT Display
PCB Coating	Standard

Drive Dimensions

Size	2
Height	10.12 in (257mm)
Width	7.4 in (188mm)
Depth	6.77 in (172 mm)
Weight	7.72 lbs (3.5 kg)
Fixings	4 x M4

Packaged Dimensions

Height	8.46 in (215mm)
Width	9.25 in (235mm)
Depth	14.76 in (375mm)
Weight	9.26 lbs (4.2 kg)



Drive color depicted doesn't reflect actual drive color

Black Outershell - RAL Name: Jet Black | RAL Number: 9005 | Hex Code #0A0A0A

Gray Door - RAL Name: Traffic White | RAL Number: 9016 | Hex Code #F6F6F6



Environmental Ratings

Humidity	14 - 104°F (-10 - 40°C) With Derating: 104 - 122°F (40 - 50°C)
Altitude	<= 1000m With Derating: <= 4000m