

P2 Series Variable Frequency Drive Datasheet

Model: P2-36150-3H04B-T

15 HP (11 kW), 17 A, 500-600 V, 3PH

IP66 Switched Outdoor Variable Frequency Drive with TFT Display

Input Ratings

Supply Voltage	500-600 V
Input Phases	3
Supply Current Continuous	20.6 A
Supply Fuse or MCB (Type B)	25 A

Output Ratings

Motor Output Rating	15 HP (11 kW)
Output Voltage	0 to Supply Voltage
Output Current	17 A

Cable Information

Max Supply Cable Size	8 AWG (8 mm ²)
Max Motor Cable Size	8 AWG (8 mm ²)
Max Motor Cable Length	328 ft (100 m)

Factory Build Options

EMC Filter	No Internal EMC
Brake Transistor	Internal
Minimum Brake Resistance	50 Ω
Enclosure	NEMA 4X (IP66) Switched
Display	TFT Display
PCB Coating	Standard

Drive Dimensions

Size	3
Height	12.2 in (310mm)
Width	8.31 in (211mm)
Depth	9.25 in (235 mm)
Weight	14.55 lbs (6.6 kg)
Fixings	4 x M4

Packaged Dimensions

Height	12.01 in (305mm)
Width	10.63 in (270mm)
Depth	17.32 in (440mm)
Weight	16.76 lbs (7.6 kg)



Drive color depicted doesn't reflect actual drive color

Black Outershell - RAL Name: Jet Black | RAL Number: 9005 | Hex Code #0A0A0A

Gray Door - RAL Name: Traffic White | RAL Number: 9016 | Hex Code #F6F6F6



Environmental Ratings

Humidity	14 - 104°F (-10 - 40°C) With Derating: 104 - 122°F (40 - 50°C)
Altitude	<= 1000m With Derating: <= 4000m