P2 Series Variable Frequency Drive Datasheet

Model: P2-42150-3HF4N-T

15 HP (11 kW), 46 A, 200-240 V, 3PH
IP55 Variable Frequency Drive with EMC Filter and TFT Display



Input Ratings

Supply Voltage	200-240 V
Input Phases	3
Supply Current Continuous	55.8 A
Supply Fuse or MCB (Type B)	63 A

Output Ratings

Motor Output Rating	15 HP (11 kW)
Output Voltage	0 to Supply Voltage
Output Current	46 A

Cable Information

Max Supply Cable Size	6 AWG (16 mm²)
Max Motor Cable Size	6 AWG (16 mm²)
Max Motor Cable Length	328 ft (100 m)

Factory Build Options

EMC Filter	Internal EMC
Brake Transistor	Internal
Minimum Brake Resistance	22 Ω
Enclosure	NEMA 12 (IP55)
Display	TFT Display
PCB Coating	Standard
Communication Protocols	ModbusRTU, CANopen, and more*

Drive Dimensions

Size	4
Height	17.72 in (450mm)
Width	6.73 in (171mm)
Depth	9.92 in (252 mm)
Weight	25.35 lbs (11.5 kg)
Fixings	4 x M8

Packaged Dimensions

Height	20.08 in (510mm)
Width	9.45 in (240mm)
Depth	12.99 in (330mm)
Weight	29.76 lbs (13.5 kg)

Drive color depicted doesn't reflect actual drive color
Black Outershell - RAL Name: Jet Black | RAL Number: 9005 | Hex Code #0A0A0A
Gray Door - RAL Name: Traffic White | RAL Number: 9016 | Hex Code #F6F6F6


Bardac Drives 40 Log Canoe Circle, Stevensville, MD 21666 USA
Phone (410) 604-3400 Fax (410) 604-3500 www.bardac.com AutomationThings.com

Environmental Ratings


Temperature	14 - 104°F (-10 - 40°C) With Derating: 104 - 122°F (40 - 50°C)
Altitude	<= 1000m With Derating: <= 4000m

* Consult factory for additional communication options.

How we measure our drives and packaging



Drive Dimensions



Package Dimensions