

P2 Series Variable Frequency Drive Datasheet

Model: P2-44250-3HF4B-T

25 HP (18.5 kW), 39 A, 380-480 V, 3PH

IP66 Switched Outdoor Variable Frequency Drive with EMC Filter and TFT Display

Input Ratings

| | |
|-----------------------------|-----------|
| Supply Voltage | 380-480 V |
| Input Phases | 3 |
| Supply Current Continuous | 47 A |
| Supply Fuse or MCB (Type B) | 63 A |

Output Ratings

| | |
|---------------------|---------------------|
| Motor Output Rating | 25 HP (18.5 kW) |
| Output Voltage | 0 to Supply Voltage |
| Output Current | 39 A |

Cable Information

| | |
|------------------------|-----------------------------|
| Max Supply Cable Size | 6 AWG (16 mm ²) |
| Max Motor Cable Size | 6 AWG (16 mm ²) |
| Max Motor Cable Length | 328 ft (100 m) |

Factory Build Options

| | |
|--------------------------|-------------------------|
| EMC Filter | Internal EMC |
| Brake Transistor | Internal |
| Minimum Brake Resistance | 22 Ω |
| Enclosure | NEMA 4X (IP66) Switched |
| Display | TFT Display |
| PCB Coating | Standard |

Drive Dimensions

| | |
|---------|--------------------|
| Size | 4 |
| Height | 14.17 in (360mm) |
| Width | 9.45 in (240mm) |
| Depth | 10.67 in (271 mm) |
| Weight | 20.94 lbs (9.5 kg) |
| Fixings | 4 x M4 |

Packaged Dimensions

| | |
|--------|---------------------|
| Height | 12.8 in (325mm) |
| Width | 11.61 in (295mm) |
| Depth | 16.73 in (425mm) |
| Weight | 25.35 lbs (11.5 kg) |

Drive color depicted doesn't reflect actual drive color

Black Outershell - RAL Name: Jet Black | RAL Number: 9005 | Hex Code #0A0A0A

Gray Door - RAL Name: Traffic White | RAL Number: 9016 | Hex Code #F6F6F6



Environmental Ratings

| | |
|----------|---|
| Humidity | 14 - 104°F (-10 - 40°C) With Derating: 104 - 122°F (40 - 50°C) |
| Altitude | <= 1000m With Derating: <= 4000m |