

P2 Series Variable Frequency Drive Datasheet

Model: P2-46300-3H04A-T

30 HP (22 kW), 34 A, 500-600 V, 3PH

IP66 Non Switched Outdoor Variable Frequency Drive with TFT Display

Input Ratings

Supply Voltage	500-600 V
Input Phases	3
Supply Current Continuous	41.2 A
Supply Fuse or MCB (Type B)	50 A

Output Ratings

Motor Output Rating	30 HP (22 kW)
Output Voltage	0 to Supply Voltage
Output Current	34 A

Cable Information

Max Supply Cable Size	6 AWG (16 mm ²)
Max Motor Cable Size	6 AWG (16 mm ²)
Max Motor Cable Length	328 ft (100 m)

Factory Build Options

EMC Filter	No Internal EMC
Brake Transistor	Internal
Minimum Brake Resistance	22 Ω
Enclosure	NEMA 4X (IP66) Non Switched
Display	TFT Display
PCB Coating	Standard

Drive Dimensions

Size	4
Height	14.17 in (360mm)
Width	9.45 in (240mm)
Depth	10.28 in (261 mm)
Weight	20.94 lbs (9.5 kg)
Fixings	4 x M4

Packaged Dimensions

Height	12.8 in (325mm)
Width	11.61 in (295mm)
Depth	16.73 in (425mm)
Weight	25.35 lbs (11.5 kg)



Drive color depicted doesn't reflect actual drive color

Black Outershell - RAL Name: Jet Black | RAL Number: 9005 | Hex Code #0A0A0A

Gray Door - RAL Name: Traffic White | RAL Number: 9016 | Hex Code #F6F6F6



Environmental Ratings

Humidity	14 - 104°F (-10 - 40°C) With Derating: 104 - 122°F (40 - 50°C)
Altitude	<= 1000m With Derating: <= 4000m