

# P2 Series Variable Frequency Drive Datasheet

Model: P2-52020-3HF42-T

**20 HP (15 kW), 60 A, 200-240 V, 3PH**  
**IP20 Variable Frequency Drive with EMC Filter and TFT Display**

## Input Ratings

Supply Voltage	200-240 V
Input Phases	3
Supply Current Continuous	70.2 A
Supply Fuse or MCB (Type B)	80 A

## Output Ratings

Motor Output Rating	20 HP (15 kW)
Output Voltage	0 to Supply Voltage
Output Current	60 A

## Cable Information

Max Supply Cable Size	2 AWG (35 mm <sup>2</sup> )
Max Motor Cable Size	2 AWG (35 mm <sup>2</sup> )
Max Motor Cable Length	328 ft (100 m)

## Factory Build Options

EMC Filter	Internal EMC
Brake Transistor	Internal
Minimum Brake Resistance	12 Ω
Enclosure	IP20
Display	TFT Display
PCB Coating	Standard
DC Choke	Included

## Drive Dimensions

Size	5
Height	19.13 in (486mm)
Width	9.17 in (233mm)
Depth	10.24 in (260 mm)
Weight	39.9 lbs (18.1 kg)
Fixings	4 x M8

## Packaged Dimensions

Height	14.02 in (356mm)
Width	13.23 in (336mm)
Depth	25.91 in (658mm)
Weight	44.31 lbs (20.1 kg)

Drive color depicted doesn't reflect actual drive color  
Black Outershell - RAL Name: Jet Black | RAL Number: 9005 | Hex Code #0A0A0A  
Gray Door - RAL Name: Traffic White | RAL Number: 9016 | Hex Code #F6F6F6



## Environmental Ratings

Humidity	14 - 122°F (-10 - 50°C)
Altitude	<= 1000m With Derating: <= 4000m