

# P2 Series Variable Frequency Drive Datasheet

Model: P2-62060-3HF4N-T

**60 HP (45 kW), 180 A, 200-240 V, 3PH**

**IP55 Variable Frequency Drive with EMC Filter and TFT Display**

## Input Ratings

Supply Voltage	200-240 V
Input Phases	3
Supply Current Continuous	163.4 A
Supply Fuse or MCB (Type B)	200 A

## Output Ratings

Motor Output Rating	60 HP (45 kW)
Output Voltage	0 to Supply Voltage
Output Current	180 A

## Cable Information

Max Supply Cable Size	300 MCM (150 mm <sup>2</sup> )
Max Motor Cable Size	300 MCM (150 mm <sup>2</sup> )
Max Motor Cable Length	328 ft (100 m)

## Factory Build Options

EMC Filter	Internal EMC
Brake Transistor	Internal
Enclosure	NEMA 12 (IP55)
Display	TFT Display
PCB Coating	Standard

## Drive Dimensions

Size	6
Height	34.06 in (865mm)
Width	12.99 in (330mm)
Depth	13.07 in (332 mm)
Weight	121.25 lbs (55 kg)
Fixings	4 x M10

## Packaged Dimensions

Height	38.58 in (980mm)
Width	17.72 in (450mm)
Depth	17.72 in (450mm)
Weight	127.87 lbs (58 kg)

Drive color depicted doesn't reflect actual drive color

Black Outershell - RAL Name: Jet Black | RAL Number: 9005 | Hex Code #0A0A0A

Gray Door - RAL Name: Traffic White | RAL Number: 9016 | Hex Code #F6F6F6



## Environmental Ratings

Ambient Temperature	14 - 104°F (-10 - 40°C)
	With Derating: 104 - 122°F (40 - 50°C)
Altitude	<= 1000m
	With Derating: <= 4000m