

V3 Series Variable Frequency Drive Datasheet

Model: V3-340240-3F1E-T

15 HP (11 kW), 24 A, 380-480 V, 3PH

IP66 With Disconnect Outdoor Variable Frequency Drive with EMC Filter and TFT Display

Input Ratings

Supply Voltage	380-480 V
Input Phases	3
Supply Current Continuous	21.6 A
Supply Fuse or MCB (Type B)	25 A

Output Ratings

Motor Output Rating	15 HP (11 kW)
Output Voltage	0 to Supply Voltage
Output Current	24 A

Cable Information

Max Supply Cable Size	8 AWG (8 mm ²)
Max Motor Cable Size	8 AWG (8 mm ²)
Max Motor Cable Length	328 ft (100 m)

Factory Build Options

EMC Filter	Internal EMC
Brake Transistor	No Brake Transistor
Enclosure	NEMA 4X (IP66) With Disconnect
Display	TFT Display
PCB Coating	Standard

Drive Dimensions

Size	3
Height	12.2 in (310 mm)
Width	8.31 in (211 mm)
Depth	9.25 in (235 mm)
Weight	14.55 lbs (6.6 kg)
Fixings	4 x M4

Packaged Dimensions

Height	12.01 in (305 mm)
Width	10.63 in (270 mm)
Depth	17.32 in (440 mm)
Weight	16.76 lbs (7.6 kg)



Drive color depicted doesn't reflect actual drive color

Black Outershell - RAL Name: Jet Black | RAL Number: 9005 | Hex Code #0A0A0A

Gray Door - RAL Name: Traffic White | RAL Number: 9016 | Hex Code #F6F6F6

