

# V3 Series Variable Frequency Drive Datasheet

Model: V3-360170-3012-T

**15 HP (11 kW), 17 A, 500-600 V, 3PH**  
**IP20 Variable Frequency Drive with TFT Display**

## Input Ratings

Supply Voltage	500-600 V
Input Phases	3
Supply Current Continuous	20.6 A
Supply Fuse or MCB (Type B)	25 A

## Output Ratings

Motor Output Rating	15 HP (11 kW)
Output Voltage	0 to Supply Voltage
Output Current	17 A

## Cable Information

Max Supply Cable Size	8 AWG (8 mm <sup>2</sup> )
Max Motor Cable Size	8 AWG (8 mm <sup>2</sup> )
Max Motor Cable Length	328 ft (100 m)

## Factory Build Options

EMC Filter	No Internal EMC
Brake Transistor	No Brake Transistor
Enclosure	IP20
Display	TFT Display
PCB Coating	Standard
Communication Protocols	BACnet, ModbusRTU, and more*

## Drive Dimensions

Size	3
Height	10.28 in (261 mm)
Width	5.16 in (131 mm)
Depth	8.07 in (205 mm)
Weight	7.72 lbs (3.5 kg)
Fixings	4 x M4

## Packaged Dimensions

Height	12.8 in (325 mm)
Width	6.5 in (165 mm)
Depth	10.24 in (260 mm)
Weight	8.16 lbs (3.7 kg)

\* Consult factory for additional communication options.

Drive color depicted doesn't reflect actual drive color  
Black Outershell - RAL Name: Jet Black | RAL Number: 9005 | Hex Code #0A0A0A  
Gray Door - RAL Name: Traffic White | RAL Number: 9016 | Hex Code #F6F6F6

