

V3 Series Variable Frequency Drive Datasheet

Model: V3-661500-301N-T

175 HP (110 kW), 150 A, 500-600 V, 3PH
IP55 Variable Frequency Drive with TFT Display

Input Ratings

Supply Voltage	500-600 V
Input Phases	3
Supply Current Continuous	160 A
Supply Fuse or MCB (Type B)	200 A

Output Ratings

Motor Output Rating	175 HP (110 kW)
Output Voltage	0 to Supply Voltage
Output Current	150 A

Cable Information

Max Supply Cable Size	300 MCM (150 mm ²)
Max Motor Cable Size	300 MCM (150 mm ²)
Max Motor Cable Length	328 ft (100 m)

Factory Build Options

EMC Filter	No Internal EMC
Brake Transistor	No Brake Transistor
Enclosure	NEMA 12 (IP55)
Display	TFT Display
PCB Coating	Standard

Drive Dimensions

Size	6
Height	34.06 in (865 mm)
Width	12.99 in (330 mm)
Depth	13.07 in (332 mm)
Weight	121.25 lbs (55 kg)
Fixings	4 x M10

Packaged Dimensions

Height	38.58 in (980 mm)
Width	17.72 in (450 mm)
Depth	17.72 in (450 mm)
Weight	127.87 lbs (58 kg)

Drive color depicted doesn't reflect actual drive color
Black Outershell - RAL Name: Jet Black | RAL Number: 9005 | Hex Code #0A0A0A
Gray Door - RAL Name: Traffic White | RAL Number: 9016 | Hex Code #F6F6F6

