

V3 Series Variable Frequency Drive Datasheet

Model: V3-843700-3R12-T

**300 HP (200 kW), 370 A, 380-480 V, 3PH
IP20 Variable Frequency Drive with TFT Display**

Input Ratings

Supply Voltage	380-480 V
Input Phases	3
Supply Current Continuous	370 A
Supply Fuse or MCB (Type B)	500 A

Output Ratings

Motor Output Rating	300 HP (200 kW)
Output Voltage	0 to Supply Voltage
Output Current	370 A

Cable Information

Max Supply Cable Size	500 MCM (240 mm ²)
Max Motor Cable Size	500 MCM (240 mm ²)
Max Motor Cable Length	328 ft (100 m)

Factory Build Options

EMC Filter	High Performance EMC Filter
Brake Transistor	No Brake Transistor
Enclosure	IP20
Display	TFT Display
PCB Coating	Standard

Drive Dimensions

Size	8
Height	38.35 in (974 mm)
Width	17.48 in (444 mm)
Depth	16.65 in (423 mm)
Weight	274.48 lbs (124.5 kg)
Fixings	4 x M12

Packaged Dimensions

Height	25.98 in (660 mm)
Width	24.41 in (620 mm)
Depth	40.16 in (1020 mm)
Weight	317.47 lbs (144 kg)

Drive color depicted doesn't reflect actual drive color
Black Outershell - RAL Name: Jet Black | RAL Number: 9005 | Hex Code #0A0A0A
Gray Door - RAL Name: Traffic White | RAL Number: 9016 | Hex Code #F6F6F6

