drive.web Datasheet

Model: dw271

speedy plug-in automation controller for PL/X Series DC Drives

I/O & Connectivity

Ethernet	100BASE-TX with drive.web peer-to-peer
Communication Protocols	ModbusRTU, ModbusTCP/IP, EIP/PCCC

Software Features

Modbus TCP/IP (04)	Slave/Server
Process Control (05)	Recommended for most applications
Winder Control (06)	Diameter Calc., Taper Tension, Torque Comp.
Math (10)	With internal 32-bit Calculator
EIP/PCCC (25)	Slave/Server
savvyPanel (26)	Operator station interface
Solar (29)	Calculates sun position azimuth and zenith
Precision Motion (39)	With Trapezoid Motion and Cam Profile

Factory Build Specs

Dimensions	1.65" x 4.13" x 0.98" (42mm x 105mm x 25mm)
Weight	Standard: 19g (0.7oz)
Mount Type	Fits onto the PL/X control board.
Operating Temperature	0°C to 50°C
Storage Temperature	-20°C to 60°C
Humidity	95% max, non-condensing
Compliance	UL, CE

Bardac Drives 40 Log Canoe Circle, Stevensville, MD 21666 USA
Phone (410) 604-3400 Fax (410) 604-3500 bardac.com AutomationThings.com