





Class 1, Division 2, Groups A, B, C, and D Hazardous Locations.





Bardac Communication Module MVI71-BDW

The MVI71 Bardac Drive module incorporates a powerful library of drive control function blocks for a wide range of applications. The Bardac drive protocol uses UDP over Ethernet to provide robust connectivity between drives, PLCs, operator stations, remote I/O and SCADA systems.

How to Contact Us: Sales and Support

All ProSoft Technology products are backed with unlimited technical support. Contact our worldwide Technical Support team directly by phone or email:

Asia Pacific

+603.7724.2080, asiapc@prosoft-technology.com Languages spoken include: Chinese, Japanese, English

Europe - Middle East - Africa

+33 (0) 5.34.36.87.20, support.EMEA@prosoft-technology.com

Languages spoken include: French, English

North America

+1.661.716.5100, support@prosoft-technology.com Languages spoken include: English, Spanish

Latin America (Sales only)

+1.281.298.9109, latinam@prosoft-technology.com Languages spoken include: Spanish, English

Brasil

.

+55-11.5084.5178, eduardo@prosoft-technology.com Languages spoken include: Portuguese, English

Bardac Communication Module

MVI71-BDW

The MVI71 Bardac Drive Interface Module allows Rockwell Automation PLC I/O compatible processors to interface easily with Bardac drive.web devices.

Features and Benefits

The MVI71-BDW module acts as a client collecting and controlling data in a Bardac drive.web compatible device. Four independent clients are contained in the module to interface with Bardac drives simultaneously. The data is passed from the network to the Rockwell Automation backplane. The data transfer from the PLC processor is asynchronous from the actions on the UDP/IP network. A 5000-word register space in the module exchanges data between the processor and the network.

General Specifications

- Single Slot 1771 backplane compatible
- The module is recognized as an Input/Output module and has access to processor memory for data transfer between processor and module
- Ladder Logic is used for data transfer between module and processor.
- Configuration data obtained through user-defined ladder. Sample ladder file included

Hardware Specifications

na ana o opcomounomo	
Specification	Description
Form Factor	Single Slot 1771 chassis compatible
	BTR/BTW data transfer
	Local or remote rack
Backplane current	800 mA @ 5 V
load	
Operating	0 to 60°C (32 to 140°F)
temperature	
Storage temperature	-40 to 85°C (-40 to 185°F)
Shock	30g operational
	50g non-operational
Vibration	5 g from 10150 Hz
Relative humidity	5 to 95% (non-condensing)
LED Indicators	Module status
	Backplane transfer status
	Application status
	Serial activity and error LED status
Configuration Serial	DB-9M PC compatible
port (CFG)	RS-232
	Hardware handshaking
Ethernet Port	RJ45 Connector
(Ethernet modules)	Link and activity LED indicators



Functional Specifications

A client configured as a Bardac master device on the MVI71-BDW module will actively issue Bardac-DW commands to other nodes on the Bardac-DW network. One hundred commands are supported for each client. The PLC processor can be programmed to control the activity on the client by actively selecting commands from the command list to execute, or issuing commands directly from the ladder logic.

Some of the general specifications include:

- Support for the storage and transfer of up to 5000 registers to/from the PLC processor's controller tags
- Module memory usage that is completely userdefinable
- Ability for the user to define commands to set or get parameters from the Bardac device
- 10/100 MB Ethernet compatible interface
- Supports up to 100 user-defined read or write commands that can be sent to a Bardac device
- Configurable parameters for the client include
 - o Error/Status Pointer
 - Command Error Pointer
 - Response Timeout
 - Retry Count

Additional Products

ProSoft Technology offers a full complement of hardware and software solutions for a wide variety of industrial communication platforms.

Visit our web site at http://www.prosoft-technology.com for a complete list of products.

Ordering Information

To order this product, please use the following:

MVI71-BDW Bardac Communication Module

To place an order, please contact your local ProSoft Technology distributor. For a list of ProSoft distributors near you, go to http://www.prosoft-technology.com

Distributors:

Place your order by email or fax to:

North American / Latin American / Asia Pacific orders@prosoft-technology.com, fax to +1 661.716.5101

Europe

.

europe@prosoft-technology.com, fax to +33 (0) 5.61.78.40.52

Copyright © ProSoft Technology, Inc. 2000 - 2007. All Rights Reserved. March 28, 2007